

# EPB 36

## 15/150 m<sup>3</sup>/h



| ITEM                      | Unit               | EPB 36        | Remarks              |
|---------------------------|--------------------|---------------|----------------------|
| <b>Boom Specs</b>         |                    |               |                      |
| Boom Type                 | -                  | 4 - R Boom    |                      |
| Horizontal reach          | m                  | 35.5          |                      |
| Reach depth               | m                  | 29.6          | including end hose   |
| End Hose                  | M                  | 3             |                      |
| Boom reach                | 1st Section        | mm            | 9,500                |
|                           | 2nd Section        | mm            | 8,600                |
|                           | 3rd Section        | mm            | 8,600                |
|                           | 4th Section        | mm            | 8,600                |
| Boom Articulation         | 1st Section        | °             | 80                   |
|                           | 2nd Section        | °             | 180                  |
|                           | 3rd Section        | °             | 180                  |
|                           | 4th Section        | °             | 240                  |
| <b>General Specs</b>      |                    |               |                      |
| Mast Height               | m                  | 20(10mx2EA)   |                      |
| Pipeline Diameter         | mm                 | 125           |                      |
| Rotation Speed            | rpm                | 0.5           |                      |
| Rotation Degree           | °                  | 370           |                      |
| Generating Power          | kW                 | 18            |                      |
| Concrete Output           | m <sup>3</sup> /hr | 15 – 150      |                      |
| Main Power                | V / Hz             | To be advised |                      |
| Control System            | Standard           | -             | Wire Remote Control  |
|                           | Option             | -             | Radio Remote Control |
| <b>Weight</b>             |                    |               |                      |
| Boom Weight               | Kg                 | 5,250         |                      |
| Pedestal + Adapter Weight | Kg                 | 5,200         |                      |



**EVERDIGM**  
La Mejor Relación Precio-Calidad  
Bombas de Concreto

